

Model		S50Q	S50D	
Cab	Type	Single Row	Single Cab 单排	Single Cab 单排
	Tilted	/	/	/
	No. of Seats	2	2	2
Dimension (mm)	Overall Dimension	5185×1735×2105	5185×1735×2060	5185×1735×2105
	Wheelbase	2650	2650	2650
	Cargo Body Dimension	3360*1615*370	3360×1615×370	3360*1615*370
	Min. Ground Clearance	150	150	150
Weight (kg)	Kerb Weight	1360	1520	1550
	Payload	1010	1350	1000
	G.V.W.	2500	3000	2600
Power	Engine Brand	LIUZHOU (Gasoline)	YUNNEI (Diesel)	QC (Diesel)
	Engine Model	LJ469Q-AE8	D19TCIE10	N485ZLQ
	Emission Standard	Euro V	Euro V (DPF)	Euro II (turbo charged)
	Displacement (cc)	1249	1910	2160
	Engine Power(Kw/rpm)	64/6000	70/3600	48/3000
	Engine Torque (N.m/rpm)	113/3500-4000	190/1800~2600	172/2000
	Gearbox Model	MR70	MT78	MT78
	Gearbox Torque (N.m)	150	210	210
	Max. Speed(km/Hr)	120	100	90
Max. Climb Ability (%)	30	35	30	
Loading	Chassis Frame Section Dimension (mm)	130*50*4	130×50×4	130*50*4
	Suspension	FR & RR Leaf Spring, 3/5	FR & RR Leaf Spring, 3/5	FR & RR Leaf Spring, 3/5
	FR&RR Axle Payload	1T/2T	1T/2T	1T/2T
	Tire Size	185R14	185R14	185R14
Brake	Serving Brake Type	Hydraulic Brake	Hydraulic Brake	Hydraulic Brake
	Parking Brake Type	Central Drum Brake	Central Drum Brake	Central Drum Brake
	ABS	●	●	/
	Front Disc Brake	●	●	●
Comfort	A/C	○	○	○
	Power Steering	●	●	●
	Front Parabolic Spring	●	●	●
	Roof Ventilation	○	○	○
	Power Window	●	●	○
Others	Voltage	12V	12V	12V
	Fuel Tank Volume	45L	40L	40L

● Standard

○ Optional